

**AD**

**MRLM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA**

**LIMÓN INTERNATIONAL AIRPORT**

**(MRLM)**

The Civil Aviation Authority informs that with an effective date of **February 20, 2025**, and **permanent**, the information of MRLM AD 2.8 Aprons, Taxiways and Check Locations/ Positions Data will be as follows:

**MRLM AD 2.8 Data on aprons, taxiways and equipment check locations/positions**

		PCR: 2160/F/B/X/T F: Pavement type (Flexible) B: Medium resistance: for rigid and flexible pavements, the typical value is E=120 MPa and includes a range of E values equal to or greater than 100 MPa and strictly less than 150 MPa X: Maximum permissible tire pressure category (X="pressure limited to 1,75 MPa") T: Evaluation method (T="technical evaluation")
1	<b>Apron designation, surface and strength</b>	
2	<b>Taxiway designation, width, surface and strength</b>	NIL
3	<b>Altimeter checkpoint location and elevation</b>	MET Office Elevation: 26 m approx.
4	<b>VOR checkpoints</b>	NIL
5	<b>INS checkpoints</b>	NIL
6	<b>Remarks</b>	NIL

**REPLACES WITH MODIFICATIONS AIRAC AIP SUP 39/24 DATED 26DEC24**